


# jot-up lite sit/stand desks datasheet

### Extent of Range

Jot-Up desks are available with height adjustable electronic lifting columns. Single and back-to-back configurations



# Certificate

BS EN 527:2002 parts 2 & 3 & BS 6396:2008.

### Delivery

This range is assembled on site by the Flexiform installation team, wrapped for protection.

### Product Warranty

7 years subject to our standard T&C's. See the Flexiform Standard Warranty document for more information

### Features

Type: Agile working height adjustable desks.

Legs: Back-to-back desks have adjoining legs with central screen support bracket. Lifting Columns: Full height adjustable electronic columns.

Upper Frame: 12swg Slide Rail support arms, welded to 12swg Folded Centre Channel.

Cable Tray: 18swg screwed to top frame assembly.

Tops: Rectangular 25mm MFC with ABS edging.

Cable Management: Cables feed up a cable slinky to the worktop cable tray which connects on desk electrics.

Standby Mode: 0.1 watts of power consumption in standby mode. Max Speed: 38mm per second (unloaded desk).Max Thrust: 1200N per column. Lifting Capacity: 800N per column (80Kg's) Sound Level: Below 55dB(A) in typical applications

Mains Voltage: 230V AC, 50Hz PVC: PVC free

Battery Operated: High performance lithium-ion battery with capacity of 2.2Ah with LED charge level indicator. Controls: Tactile Up/Down switch Sensors: Integrated sensor minimising the risk of damage to hard object. Levelling Feet: Included. Optional Software Features Software Connection: Cable connects

computer to the desk. Reminders: Prompts the user to stand a selected percentage of an hour, every hour.

Display: Displays current desk height. User Statistics: Counts calories burned while standing and minuites standing. Memory Positions: Up to 3 memory positions.

Languages: English, German, French, Spanish, Italian, Korean, Chinese and Japanese.

Computer Compatability: Mac, PC and Surface tablets (Windows 7, Windows 8 or higher or Mac OS (minimum OS 10.7). Data: Statistics can be exported to Excel sheets.

### **Optional Components**

Screens, CPU holder, Lithium Ion Battery Pack, Colour Accent Disks, and Spacing Brackets to ensure a row of desks comply with the relevant safety standards.

# flexiform

### Dimensions

Fixed Height: 740mm. Height Settable: 665mm - 1015mm. Height Adjustable: 610mm - 1260mm. Widths: 970mm, 1170mm, 1370mm, 1570mm, 1770mm. Single Desk Depth: 780mm. Back-to-Back Desk Depth: 1650mm.

### Materials

MFC Top Panels: 25mm melamine faced chipboard (M.F.C) with 2mm ABS matching edging or contrasting edging. British standard 476 class 1 surface spread of flame. Meets E1 European standards on Formladehyde emissions.

Steel: Powder coated steel with minimum paint coverage thickness of 35 Microns. Indentation, cross cut+adhesion and bend tested.

Product Environmental Certification



#### MFC Band 1 Finishes













White 25mm MFC with contrasting oak edge. Code: WHO

Walnut 25mm MFC with matching

White 25mm MFC with matching

Grey 25mm MFC with matching

Dust Grey 25mm MFC with matching

Oak 25mm MFC with matching edge.

edge. Code: WHM

edge. Code: MOG

edge. Code: DGM

edge. Code: MOW\*

Code: MOK\*

White 25mm MFC with contrasting black edge. Code: WHB

\*Please note, we cannot guarantee continuity of these finishes.

## MFC Band 2 Finishes



Denim Blue 25mm MFC with matching edge. Code: MDB

Reed Green 25mm MFC with matching edge. Code: MRG





Natu

Natural Nebraska Oak 25mm MFC with matching edge. Code: MNO



Natural Hamilton Oak 25mm MFC with matching edge. Code: MHO



Truffle Brown Denver Oak 25mm MFC with matching edge. Code: MDO



Natural Carini Walnut 25mm MFC with matching edge. Code: MCW



Light grey Chicago Concrete 25mm MFC with matching edge. Code: MCC

### Lifting Column & Frame Steel Finishes

Silver. RAL9006 Code: JOS

> White. RAL9016 Code: JWS

