


Extent of Range

Metal ventilated lockers with 1, 2, 3 or 4 doors.



Delivery

These lockers are delivered pre-assembled by the Flexiform installation team, wrapped for protection.

Product Warranty

15 years subject to our standard T&C's. See the Flexiform Standard Warranty document for more information.

Features

Type: Ventilated lockers.

Steel Carcass: 18 gauge steel with 20swg inner panels.

Panel Finish: Paint finish is either Epoxy or Epoxy/Polyester mix powder coating sprayed electrostatically. Film build is nominally 35-50 microns. All finishes are stoved to the appropriate BS3900 specification.

Doors: 18 gauge steel with stiffening rails to ensure integrity.

Locks: Cam lock or padlockable locks. Hinges: Designed for 120 degree opening ensuring clear access space for users. Levelling: Floor levelling feet supplied in

galvanised steel lockers.

Ventilation: Perforated ventilation panels in

Components

1 Door Locker: 1 fixed shelf and 2 coat hooks

2 Door Locker: 2 coat hooks per

compartment.

3 Door Locker: Empty compartments. 4 Door Locker: Empty compartments.

Dimensions

Height: 1800mm.

Widths: 300mm and 450mm. Depths: 300mm and 450mm.

Optional Accessories: Sloping tops and cladding panel.



Materials

Steel: Powder coated steel with minimum paint coverage thickness of 35 Microns. Indentation, cross cut+adhesion and bend tested.

Anti-Bacterial Steel

Standard steel finishes with anti-bacterial coating.

Chilli Red RAL3001

Code: SCRB



Steel Finishes

Standard Flexiform finishes. Additional colour options available (may incur an upcharge).






Code: JOS


















Signal Blue. RAL5005
Code: SBS











Product Environmental Certification





Product Recyclable Content

Approximately 98% recyclable.

Product Certification

BS 4875-7:2006, BS EN 14074:2004, BS EN 14073-3:2004, BS EN 14073-2:2004.

