

meira back-to-back desk datasheet

Extent of Range

Meira back-to-back desks are available with goalpost (straight) legs and rectangular tops only. Starter and extension desks.



Delivery

This range is delivered in components, wrapped for protection and assembled by the Flexiform installation team.

Product Warranty

15 years subject to our standard T&C's. See the Flexiform Standard Warranty document for more information.

Product Certificate

BS EN ISO 9241, 1999, Part 5: Workstation Layout and Postural Requirements. BS EN 527, 2011; Part 1 Dimensions as Fixed Height Desk, Type C. BE EN 527-2: 2016 + A1:2019 Safety, Strength & Durability.

Type: Desk

Type: 2-person workstation with 2-person extensions. Eg. 2 persons, 4 persons, 6 persons. Extensions are unlimited. Contact Flexiform for details.

Beams: Formed from 40mm x 20mm tube for strength.

Legs: 40mm x 40mm tube for strength. Goalpost/ straight design.

Tops: 25mm MFC top with 2mm ABS edge, sliding top for cable access. Tops are 5mm narrower than the length of the footprint to maximise material optimisation

Tested to: Over 200kg of imposed load with minimal deflection.

Optional Cable Tray: High-capacity cable tray, 130mm deep with plastic cable clamps for safety. Cable tray features holes allowing liquid to escape quickly in case of an accident.

Optional Cable Tower: Vertical all-steel cable tower in the centre of the desk to feed cables from the floor into cable trays.

Optional Screens: Attach directly to the frame using a screen bracket. Screens are not included. Please see Flexiform member of staff for compatibility requirements.

Dimensions

Height: 740mm. Widths: 1200mm, 1400mm and 1600mm (per workstation). Depth: 1650mm (800mm per workstation).

Components

Desk-mounted screens, infill tubes, cable leg covers for intermediate legs and cable trays.

Materials

MFC Top Panels: 25mm melamine faced chipboard (M.F.C) with 2mm ABS matching edging or contrasting edging. British standard 476 class 1 surface spread of flame. Meets E1 European standards on Formladehyde emissions.

Steel: Powder coated steel with minimum paint coverage thickness of 35 Microns. Indentation, cross cut+adhesion and bend tested.

flexiform

MFC Band 1 Finishes White 25mm MFC with matching edge. Code: WHM Grey 25mm MFC with matching edge. Code: MOG Dust Grey 25mm MFC with matching edge. Code: DGM Code: MOK*

Oak 25mm MFC with matching edge.



Walnut 25mm MFC with matching edge. Code: MOW*



White 25mm MFC with contrasting oak edge. Code: WHO



White 25mm MFC with contrasting black edge. Code: WHB

*Please note, we cannot guarantee continuity of these finishes.

MFC Band 2 Finishes



Cashmere Grey 25mm MFC with matching edge. Code: MSC

Antique Rose 25mm MFC with matching edge. Code: MAR





Reed Green 25mm MFC with matching edge. Code: MRG



Sevilla Ash 25mm MFC with matching edge. Code: MSA



Natural Nebraska Oak 25mm MFC with matching edge. Code: MNO



Natural Hamilton Oak 25mm MFC with matching edge. Code: MHO



Truffle Brown Denver Oak 25mm MFC with matching edge. Code: MDO



Natural Carini Walnut 25mm MFC with matching edge. Code: MCW

Light grey Chicago Concrete 25mm MFC with matching edge. Code: MCC

Standard Steel Finishes.





Graphite Grey. RAL7024. Matt Code: GGM

Silver. RAL9006. Matt Code: JOM

Black. RAL9005. Matt.

Pale Grey. RAL7035. Matt Code: PGM

White. RAL9016. Matt Code: JWM

Pale Brown. RAL8025. Matt Code: BPM

Grey Beige. RAL1019. Matt Code: BGM

Beige. BS10B19. Matt Code: BBM

Light Ivory. RAL1015. Matt Code: BIM

Olive Green. RAL6003. Matt Code: GOM

Fern Green. RAL6025. Matt Code: GFM

Reed Green. RAL6013. Matt Code: GRM

Black Green. RAL6012. Matt Code: GBM

Pine Green. RAL6028. Matt Code: GPM

Patina Green. RAL6000. Matt Code: GAM

Pale Green. RAL6021. Matt Code: GCM



Standard Steel Finishes Continued.

Yellow Red. RAL2000. Matt Code: OYM

Broom Yellow. RAL1032. Matt Code: YBM

Product Environmental Certification



Product Recyclable Content 99.95% recyclable 61.07% recycled content

flexiform









